

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 000000000050583096      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans  
Product code : 000000000050583096  
Unique Formula Identifier (UFI) : SV1C-W4YG-3005-MU67

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Spraying hardener

#### 1.3 Details of the supplier of the safety data sheet

**Company:**  
BASF Coatings France SAS  
Z.I de Breuil-Le-Sec, Rue André Pomery  
60480 Breuil-Le-Sec  
France

**Contact address:**  
BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

Telephone: +44 161 475 3000  
E-mail address: product-safety-coatings@basf.com

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Flammable liquids, Category 3

H226: Flammable liquid and vapor.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry



## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                  |                                 |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number:      | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830 | Date of first issue: 25.04.2025 |
|         |                | 96               |                                 |

|  |  |
|--|--|
| Acute toxicity, Category 4   | H332: Harmful if inhaled.                  |
| Skin sensitization, Category 1   | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.   |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.    |

### 2.2 Label elements

**Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

|                          |   |  |
|--------------------------|---|--|
| Hazard pictograms        | : |    |
| Signal Word              | : | Warning  |
| Hazard Statements        | : | H226 Flammable liquid and vapor.<br>H317 May cause an allergic skin reaction.<br>H332 Harmful if inhaled.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.   |
| Precautionary Statements | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P261 Avoid breathing mist or vapors.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.<br><b>Response:</b><br>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.<br>P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.<br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

Hazardous ingredients which must be listed on the label:  
Hexamethylen-1,6-diisocyanat Homopolymer  
1-methoxy-2-propylacetate  
n-Butyl acetate

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830-96      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025

xylene

### Additional Labeling

EUH204      Contains isocyanates. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature      :      organic solvent  
polyisocyanate

### Components

| Chemical name                            | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number  | Classification  | Concentration<br>(% w/w) |
|--|--|---|--------------------------|
| Hexamethylen-1,6-diisocyanat Homopolymer | 28182-81-2<br>01-2119485796-17   | Acute Tox. 4; H332<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>(Respiratory system) | >= 25 - < 50             |
| 1-methoxy-2-propylacetate                | 108-65-6<br>203-603-9<br>607-195-00-7<br>UK-20-9702550300-0-0000<br>UK-20-0537843089-5-0000<br>UK-20-9642318150-0-0000 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)                   | >= 20 - < 25             |
| n-Butyl acetate                          | 123-86-4<br>204-658-1<br>607-025-00-1<br>UK-20-9702550300-0-0000<br>UK-20-0537843089-                                  | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)                   | >= 15 - < 20             |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
96

|                  |  |  |                 |
|------------------|--|--|-----------------|
|                  | 5-0000<br>UK-20-9642318150-0-0000  |  |                 |
| xylene           | 1330-20-7<br>215-535-7<br>601-022-00-9<br>UK-20-2749242067-7-0000<br>UK-20-9702550300-0-0000<br>UK-20-0537843089-5-0000<br>UK-20-9642318150-0-0000 | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br>(Kidney, Liver, Central nervous system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3; H412 | $\geq 7 - < 10$ |
| ethylbenzene     | 100-41-4<br>202-849-4<br>601-023-00-4<br>UK-20-9702550300-0-0000<br>UK-20-0537843089-5-0000  | Flam. Liq. 2; H225<br>Acute Tox. 4; H332<br>STOT RE 2; H373<br>(Auditory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3; H412   | $\geq 1 - < 2$  |
| isobutyl acetate | 110-19-0<br>203-745-1<br>607-026-00-7<br>UK-20-0537843089-5-0000<br>UK-20-9642318150-0-0000  | Flam. Liq. 2; H225<br>STOT SE 3; H336<br>(Central nervous system)  | $\geq 1 - < 2$  |

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.  
Move out of dangerous area.  
In all cases of doubt, or when symptoms persist, seek medical attention.  
Immediately remove contaminated clothing.  
If the patient is likely to become unconscious, place and

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                  |                                 |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number:      | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830 | Date of first issue: 25.04.2025 |
|         |                | 96               |                                 |

transport in stable sideways position (recovery position).  
First aid personnel should pay attention to their own safety.

- If inhaled : If breathed in, move person into fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Do NOT use solvents or thinners.  
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If symptoms persist, call a physician.
- If swallowed : Rinse mouth.  
Do NOT induce vomiting.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
- Risks : May cause an allergic skin reaction.  
Harmful if inhaled.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No known specific antidote.  
Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Dry powder  
Foam  
Carbon dioxide (CO<sub>2</sub>)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830<br>96 | Date of first issue: 25.04.2025 |

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Cool containers/tanks with water spray.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth.  
Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                  |                                 |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number:      | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830 | Date of first issue: 25.04.2025 |
|         |                | 96               |                                 |

One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.  
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).  
Do not return residues to the storage containers.  
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good industrial hygiene and safety practice.  
Do not breathe vapors or spray mist.
- Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
96

clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted. Use explosion-proof equipment.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.  
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature : 5.00 - 35.00 °C

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)  
Suitable material: Stainless steel 1.4301 (V2)  
Suitable material: Stove-lacquer R 78433, Stove-lacquer EHD0022, Stove-lacquer RDL 50, Stove-lacquer C222A/C221A, Stove-lacquer 79/14/3 (Müller/CH), Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X  
Suitable material: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP)

### 7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parameters | Basis |
|------------|---------|------------------|--------------------|-------|
|------------|---------|------------------|--------------------|-------|

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 000000000505830      Date of last issue: 07.06.2025  
96      Date of first issue: 25.04.2025

|  |  | of exposure) |                                  |                  |
|--|--|--------------|----------------------------------|------------------|
| Hexamethylen-1,6-diisocyanat Homopolymer | 28182-81-2   | TWA          | 0.02 mg/m <sup>3</sup><br>(NCO)  | GB EH40          |
|  | Further information: Capable of causing occupational asthma.   |              |                                  |                  |
|  |  | STEL         | 0.07 mg/m <sup>3</sup><br>(NCO)  | GB EH40          |
|  | Further information: Capable of causing occupational asthma.   |              |                                  |                  |
| 1-methoxy-2-propylacetate                | 108-65-6   | TWA          | 50 ppm<br>274 mg/m <sup>3</sup>  | GB EH40          |
|  | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |              |                                  |                  |
|  |  | STEL         | 100 ppm<br>548 mg/m <sup>3</sup> | GB EH40          |
|  | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |              |                                  |                  |
|  |  | STEL         | 100 ppm<br>550 mg/m <sup>3</sup> | 2000/39/EC       |
|  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |              |                                  |                  |
|  |  | TWA          | 50 ppm<br>275 mg/m <sup>3</sup>  | 2000/39/EC       |
|  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |              |                                  |                  |
| n-Butyl acetate                          | 123-86-4   | TWA          | 150 ppm<br>724 mg/m <sup>3</sup> | GB EH40          |
|  |  | STEL         | 200 ppm<br>966 mg/m <sup>3</sup> | GB EH40          |
|  |  | STEL         | 150 ppm<br>723 mg/m <sup>3</sup> | 2019/1831/E<br>U |
|  | Further information: Indicative  |              |                                  |                  |
|  |  | TWA          | 50 ppm<br>241 mg/m <sup>3</sup>  | 2019/1831/E<br>U |
|  | Further information: Indicative  |              |                                  |                  |
| xylene                                   | 1330-20-7  | TWA          | 50 ppm<br>220 mg/m <sup>3</sup>  | GB EH40          |
|  | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |              |                                  |                  |
|  |  | STEL         | 100 ppm<br>441 mg/m <sup>3</sup> | GB EH40          |
|  | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will                            |              |                                  |                  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
96      Date of first issue: 25.04.2025

|                  |  |                            |                                  |                  |
|------------------|--|----------------------------|----------------------------------|------------------|
|                  |  | lead to systemic toxicity. |                                  |                  |
|                  |  | TWA                        | 50 ppm<br>221 mg/m <sup>3</sup>  | 2000/39/EC       |
|                  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                            |                                  |                  |
|                  |  | STEL                       | 100 ppm<br>442 mg/m <sup>3</sup> | 2000/39/EC       |
|                  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                            |                                  |                  |
| ethylbenzene     | 100-41-4   | TWA                        | 100 ppm<br>441 mg/m <sup>3</sup> | GB EH40          |
|                  | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                            |                                  |                  |
|                  |  | STEL                       | 125 ppm<br>552 mg/m <sup>3</sup> | GB EH40          |
|                  | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                            |                                  |                  |
|                  |  | TWA                        | 100 ppm<br>442 mg/m <sup>3</sup> | 2000/39/EC       |
|                  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                            |                                  |                  |
|                  |  | STEL                       | 200 ppm<br>884 mg/m <sup>3</sup> | 2000/39/EC       |
|                  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                            |                                  |                  |
| isobutyl acetate | 110-19-0   | TWA                        | 150 ppm<br>724 mg/m <sup>3</sup> | GB EH40          |
|                  |  | STEL                       | 187 ppm<br>903 mg/m <sup>3</sup> | GB EH40          |
|                  |  | TWA                        | 50 ppm<br>241 mg/m <sup>3</sup>  | 2019/1831/E<br>U |
|                  | Further information: Indicative  |                            |                                  |                  |
|                  |  | STEL                       | 150 ppm<br>723 mg/m <sup>3</sup> | 2019/1831/E<br>U |
|                  | Further information: Indicative  |                            |                                  |                  |

### Biological occupational exposure limits

| Substance name                            | CAS-No.    | Control parameters  | Sampling time                        | Basis          |
|---|------------|---|--------------------------------------|----------------|
| Hexamethylen-1,6-diiisocyanat Homopolymer | 28182-81-2 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40<br>BAT |
| xylene                                    | 1330-20-7  | methyl hippuric   | After shift                          | GB EH40        |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
96      Date of first issue: 25.04.2025

|  |  |  |  |     |
|--|--|--|--|-----|
|  |  | acid: 650 Millimoles per mole creatinine (Urine) |  | BAT |
|--|--|--|--|-----|

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation.

#### Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.  
Safety glasses with side-shields conforming to EN166

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm  
Further information on penetration time is available from the manufacturer of the glove.  
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Request information on glove permeation properties from the glove supplier.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
Preventive skin protection  
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)  
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):  
Suitable materials against splashes (recommended: At least

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830<br>96 | Date of first issue: 25.04.2025 |

---

|                          |   |  |
|--------------------------|---|--|
| Skin and body protection | : | protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)<br>Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres. chemical-resistant disposable coveralls  |
| Respiratory protection   | : | Suitable respiratory equipment:<br>full face mask with AB2P3 class combination filter<br>In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.<br>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.   |
| Protective measures      | : | Do not breathe vapour/spray.<br>Eye wash fountains and safety showers must be easily accessible.<br><br>If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.<br><br>Avoid contact with the skin, eyes and clothing.<br>Handle in accordance with good industrial hygiene and safety practice. |

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|  |   |  |
|--|---|--|
| Appearance                                       | : | liquid                                 |
| Color  | : | colorless                              |
| Odor   | : | pungent                                |
| pH   | : | substance/mixture is non-polar/aprotic |
| Melting point/freezing point                     | : | not determined                         |
| Boiling point/boiling range                      | : | 115.00 - 195.00 °C                     |
| Flash point                                      | : | 23 °C<br>Method: ISO 3679              |
| Upper explosion limit / Upper flammability limit | : | not determined                         |
| Lower explosion limit / Lower flammability limit | : | > 35.0 g/m <sup>3</sup>                |
| Vapor pressure                                   | : | 6.4000 hPa (20 °C)                     |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                  |                                 |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number:      | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830 | Date of first issue: 25.04.2025 |
|         |                | 96               |                                 |

---

|  |   |   |
|--|---|---|
|  |   | not determined (50 °C)  |
| Density                                | : | 1.022 g/cm <sup>3</sup> (20 °C)                                 |
| Solubility(ies)                        |   |   |
| Water solubility                       | : | not determined  |
| Partition coefficient: n-octanol/water | : | not applicable for mixtures                                     |
| Autoignition temperature               | : | > 200 °C  |
| Decomposition temperature              | : | No decomposition if stored and handled as prescribed/indicated. |
| Viscosity                              |   |   |
| Viscosity, kinematic                   | : | not determined (40 °C)  |
|  |   | 7.3 mm <sup>2</sup> /s (23 °C)                                  |
| Flow time                              | : | > 30 s at 23 °C   |
|  |   | Cross section: 3 mm   |
|  |   | Method: ISO 2431  |
| Explosive properties                   | : | Not explosive   |
| Oxidizing properties                   | : | The substance or mixture is not classified as oxidizing.        |

### 9.2 Other information

|                         |   |  |
|-------------------------|---|--|
| Flammability (liquids)  | : | Flammable liquid and vapour.   |
| Self-heating substances | : | The substance or mixture is not classified as self heating.                  |
| Metal corrosion rate    | : | Not corrosive to metals.   |
| Particle size           | : | The substance / product is marketed or used in a non solid or granular form. |

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830<br>96 | Date of first issue: 25.04.2025 |

---

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Protect from frost.  
Avoid direct sunlight.  
Heat.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Harmful if inhaled.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: 18.88 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Components:

##### n-Butyl acetate:

Assessment : Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                  |                                 |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number:      | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830 | Date of first issue: 25.04.2025 |
|         |                | 96               |                                 |

### **isobutyl acetate:**

Assessment : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration toxicity**

Based on available data, the classification criteria are not met.

#### **Product:**

No aspiration toxicity classification

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
Date of first issue: 25.04.2025  
96

### 12.3 Bioaccumulative potential

#### Components:

##### **Hexamethylen-1,6-diisocyanat Homopolymer:**

Partition coefficient: n-octanol/water : log Pow: 9.81 (25 °C)

##### **1-methoxy-2-propylacetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)  
pH: 6.8  
Method: OECD Test Guideline 117  
GLP: yes

##### **n-Butyl acetate:**

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)  
log Pow: 2.3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

##### **xylene:**

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)  
GLP: no  
Remarks: Information taken from reference works and the literature.

##### **ethylbenzene:**

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)  
log Pow: 3.6 (20 °C)  
pH: 7.8  
GLP: yes

##### **isobutyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
96      Date of first issue: 25.04.2025

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

---

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1866  
ADR : UN 1866  
RID : UN 1866  
IMDG : UN 1866  
IATA : UN 1866

### 14.2 UN proper shipping name

ADN : RESIN SOLUTION  
ADR : RESIN SOLUTION  
RID : RESIN SOLUTION

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
96      Date of first issue: 25.04.2025

**IMDG** : RESIN SOLUTION

**IATA** : RESIN SOLUTION

### 14.3 Transport hazard class(es)

|             | Class | Subsidiary risks |
|-------------|-------|------------------|
| <b>ADN</b>  | : 3   |                  |
| <b>ADR</b>  | : 3   |                  |
| <b>RID</b>  | : 3   |                  |
| <b>IMDG</b> | : 3   |                  |
| <b>IATA</b> | : 3   |                  |

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passen-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
96      Date of first issue: 25.04.2025

ger aircraft)  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable liquid

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : no

**ADR**  
Environmentally hazardous : no

**RID**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:  
Number on list 3, 20

Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                        |                                 |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:            | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830<br>96 | Date of first issue: 25.04.2025 |

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

P5c

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 50.66 %

Volatile organic compounds (VOC) content: 517.74 g/l  
VOC content excluding water

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

## SECTION 16: Other information

### Full text of H-Statements

|      |   |
|------|---|
| H225 | : Highly flammable liquid and vapor.            |
| H226 | : Flammable liquid and vapor.                   |
| H304 | : May be fatal if swallowed and enters airways. |
| H312 | : Harmful in contact with skin.                 |
| H315 | : Causes skin irritation.                       |
| H317 | : May cause an allergic skin reaction.          |
| H319 | : Causes serious eye irritation.                |
| H332 | : Harmful if inhaled.                           |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

Version 1.2      Revision Date: 17.12.2025      SDS Number: 0000000000505830      Date of last issue: 07.06.2025  
96      Date of first issue: 25.04.2025

H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 BAT : UK. Biological monitoring guidance values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 51-520 2,5L 2K Hardener CV Normal 2,5L Steel jerricans

|         |                |                  |                                 |
|---------|----------------|------------------|---------------------------------|
| Version | Revision Date: | SDS Number:      | Date of last issue: 07.06.2025  |
| 1.2     | 17.12.2025     | 0000000000505830 | Date of first issue: 25.04.2025 |
|         |                | 96               |                                 |

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

#### Classification of the mixture:

|              |      |
|--------------|------|
| Flam. Liq. 3 | H226 |
| Acute Tox. 4 | H332 |
| Skin Sens. 1 | H317 |
| STOT SE 3    | H336 |
| STOT SE 3    | H335 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN