

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Product code : 000000000050583129

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying
Substance/Mixture : hardener

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings France SAS
Z.I de Breuil-Le-Sec, Rue André Pommery
60480 Breuil-Le-Sec
France

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary
Statements

:

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing mist or vapors.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

P301 + P310 IF SWALLOWED: Immediately call a
POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical
or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

Hexamethylen-1,6-diisocyanat Homopolymer

1-methoxy-2-propylacetate

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)

2-butoxyethyl acetate

Additional Labeling

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylen-1,6-diisocyanat Homopolymer	28182-81-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317	>= 25 - < 50

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow
2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 25.04.2023
2.0 25.04.2025 000000000050583 Date of first issue: 25.04.2023
129

		STOT SE 3; H335 (Respiratory system)	
1-methoxy-2-propylacetate	108-65-6 203-603-9 607-195-00-7 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 12.5 - < 15
Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0)	64742-95-6 918-668-5	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 12.5

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow
2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

	UK-20-0537843089-5-0000	(Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 10 - < 12.5

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version 2.0 Revision Date: 25.04.2025 SDS Number: 000000000050583129 Date of last issue: 25.04.2023
Date of first issue: 25.04.2023

	UK-20-9642318150-0-0000		
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 5 - < 7

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Immediately remove contaminated clothing.
In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Never give anything by mouth to an unconscious person.
Keep patient warm and at rest.

If inhaled : If breathed in, move person into fresh air.
Call a physician or poison control center immediately.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : If symptoms persist, call a physician.
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Do NOT use solvents or thinners.

In case of eye contact : If symptoms persist, call a physician.

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If swallowed : Do not induce vomiting due to aspiration hazard.

Keep at rest.

If symptoms persist, call a physician or Poison Control Center immediately.

Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

available in Section 2 and in the Toxicological assessments available in Section 11.

Risks : May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

4.3 Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : In the event of fire, cool tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately.
This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection
against fire and explosion

: Avoid all sources of ignition: heat, sparks, open flame.
Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage : 5 - 35 °C

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow
2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 25.04.2023
2.0 25.04.2025 000000000050583 Date of first issue: 25.04.2023
129

	Further information: Capable of causing occupational asthma.			
		STEL	0.07 mg/m ³ (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			
1-methoxy-2-propylacetate	108-65-6	TWA	50 ppm 274 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm	2000/39/EC

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow
2,5L Steel jerricans

Version 2.0 Revision Date: 25.04.2025 SDS Number: 00000000050583
129 Date of last issue: 25.04.2023 Date of first issue: 25.04.2023

			241 mg/m3	EU
Further information: Indicative				
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m3	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	50 ppm 332 mg/m3	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	50 ppm 333 mg/m3	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version 2.0 Revision Date: 25.04.2025 SDS Number: 00000000050583 129 Date of last issue: 25.04.2023 Date of first issue: 25.04.2023

		TWA	20 ppm 133 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylen-1,6-diisocyanat Homopolymer	28182-81-2	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	00000000050583 129	Date of first issue: 25.04.2023

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

full face mask with AB2P3 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	pungent
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
Boiling point/boiling range	:	124 - 195 °C Method: calculated
Flash point	:	23 °C

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Method: ISO 3679

Upper explosion limit / Upper
flammability limit : not determined

Lower explosion limit / Lower
flammability limit : > 35 g/m³

Vapor pressure : 4.5000 hPa (20 °C)
Method: other (calculated)
not determined (50 °C)

Relative vapor density : Heavier than air.

Density : 1.020 g/cm³ (20 °C)

Solubility(ies)

Water solubility : not determined
Partition coefficient: n-
octanol/water : not applicable for mixtures

Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as
prescribed/indicated.

Viscosity

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Viscosity, kinematic	:	not determined (40 °C) 7.3 mm ² /s (23 °C)
Flow time	:	> 30 s at 23 °C Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids)	:	Flammable liquid and vapour.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Protect from frost.
Heat, flames and sparks.
Heat.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 19.84 mg/l
Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Components:

n-Butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Hexamethylen-1,6-diisocyanat Homopolymer:

Partition coefficient: n- : log Pow: 9.81 (25 °C)
octanol/water

1-methoxy-2-propylacetate:

Partition coefficient: n- : log Pow: 1.2 (20 °C)
octanol/water

pH: 6.8

Method: OECD Test Guideline 117

GLP: yes

Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):

Partition coefficient: n- : log Pow: 3.17
octanol/water

GLP: no

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

n-Butyl acetate:

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)
log Pow: 2.3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.51 (25 °C)
pH: 7
Method: OECD Test Guideline 107
GLP: no

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be
disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed
of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1866
ADR	: UN 1866
RID	: UN 1866

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

IMDG : UN 1866

IATA : UN 1866

14.2 UN proper shipping name

ADN : RESIN SOLUTION

ADR : RESIN SOLUTION

RID : RESIN SOLUTION

IMDG : RESIN SOLUTION

IATA : RESIN SOLUTION

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : III

Classification Code : F1

Hazard Identification
Number : 30

Labels : 3

ADR

Packing group : III

Classification Code : F1

Hazard Identification : 30

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Number

Labels : 3

Tunnel restriction code : (D/E)

RID

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable liquid

14.5 Environmental hazards

ADN

Environmentally hazardous	: no
---------------------------	------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:
Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Volatile organic compounds (VOC) content: 515 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	00000000050583 129	Date of first issue: 25.04.2023

control)

Volatile organic compounds (VOC) content: 50.5 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	00000000050583 129	Date of first issue: 25.04.2023

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H317 : May cause an allergic skin reaction.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitization
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first
list of indicative occupational exposure limit values
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a
fifth list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	000000000050583 129	Date of first issue: 25.04.2023

Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

51-530 2,5L 2K Hardener CV Slow 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 25.04.2023
2.0	25.04.2025	00000000050583 129	Date of first issue: 25.04.2023

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN