

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 000000000050669596      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums  
Product code : 000000000050669596  
Unique Formula Identifier (UFI) : HAG5-H1V2-C009-85Y3

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Spraying hardener

#### 1.3 Details of the supplier of the safety data sheet

**Company:**  
BASF Coatings France SAS  
Z.I de Breuil-Le-Sec, Rue André Pomery  
60480 Breuil-Le-Sec  
France

**Contact address:**  
BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

Telephone: +44 161 475 3000  
E-mail address: product-safety-coatings@basf.com

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Acute toxicity, Category 4

H332: Harmful if inhaled.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695 96	Date of first issue: 05.09.2024

Eye irritation, Category 2  
Skin sensitization, Category 1  
Specific target organ toxicity - single exposure, Category 3, Respiratory system  
Long-term (chronic) aquatic hazard, Category 3

H319: Causes serious eye irritation.  
H317: May cause an allergic skin reaction.  
H335: May cause respiratory irritation.  
H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

**Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P261 Avoid breathing mist or vapors.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Hazardous ingredients which must be listed on the label:

Hexamethylen-1,6-diisocyanat Homopolymer  
| 2-heptanone  
| isophorone diisocyanate (IPDI) polymer  
| 1,6-hexamethylene diisocyanate

### Additional Labeling



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

	01-2119488734-24	(Respiratory system)	
3,5,5-trimethylhexanoic acid	3302-10-1 221-975-0 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 1 - < 2
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 1 - < 2
1,6-hexamethylene diisocyanate	822-06-0 212-485-8 615-011-00-1 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)  specific concentration limit Resp. Sens. 1; H334 >= 0.5 % Skin Sens. 1; H317 >= 0.5 %	< 0.1

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

---

transport in stable sideways position (recovery position).  
Immediately remove contaminated clothing.  
In all cases of doubt, or when symptoms persist, seek medical attention.  
Move out of dangerous area.  
Never give anything by mouth to an unconscious person.

- If inhaled : If breathed in, move person into fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
If symptoms persist, call a physician.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Call a physician immediately.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.  
Call a physician immediately.  
If easy to do, remove contact lens, if worn.
- If swallowed : Rinse mouth with water.  
Do not induce vomiting due to aspiration hazard.  
Keep at rest.  
If swallowed, call a poison control center or doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
- Risks : May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause respiratory irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No known specific antidote.  
Treat symptomatically.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695 96	Date of first issue: 05.09.2024

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Dry powder  
Foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

#### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Cool containers/tanks with water spray.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

#### 6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.  
Avoid subsoil penetration.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695	Date of first issue: 05.09.2024
		96	

Do not allow uncontrolled discharge of product into the environment.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

### 6.4 Reference to other sections

For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).  
Do not return residues to the storage containers.  
Smoking, eating and drinking are forbidden in application areas. For personal protection see section 8. Comply with the health and safety at work laws.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good industrial hygiene and safety practice.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695	Date of first issue: 05.09.2024
		96	

Open drum carefully as content may be under pressure. Do not breathe vapors or spray mist. Protect from moisture.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted. Use explosion-proof equipment.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Exercise caution when opening to allow pressure release. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation. Always keep in containers of same material as the original one. Observe label precautions.

Advice on common storage : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

### 7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
96      Date of first issue: 05.09.2024

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylen-1,6-diisocyanat Homopolymer	28182-81-2	TWA	0.02 mg/m <sup>3</sup> (NCO)	GB EH40
		Further information: Capable of causing occupational asthma.		
		STEL	0.07 mg/m <sup>3</sup> (NCO)	GB EH40
		Further information: Capable of causing occupational asthma.		
2-heptanone	110-43-0	STEL	100 ppm 475 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	50 ppm 237 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	50 ppm 238 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 475 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	50 ppm 332 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	50 ppm 333 mg/m <sup>3</sup>	2000/39/EC

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 000000000506695      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 133 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
1,6-hexamethylene diisocyanate	822-06-0	TWA	0.02 mg/m <sup>3</sup> (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL	0.07 mg/m <sup>3</sup> (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylen-1,6-diisocyanat Homopolymer	28182-81-2	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT
1,6-hexamethylene diisocyanate	822-06-0	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

### Derived No Effect Level (DNEL)

Substance name	End Use	Routes of exposure	Potential health effects	Value
Ethyl 3-ethoxypropionate	Workers	Skin contact	Long-term systemic effects	102 mg/kg
	Workers	Inhalation	Long-term systemic effects	610 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term local effects	102 mg/cm <sup>2</sup>
	Workers	Inhalation	Long-term local effects	610 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	24.2 mg/kg
	Consumers	Inhalation	Long-term systemic effects	72.6 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	1.2 mg/kg

### Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
96      Date of first issue: 05.09.2024

Ethyl 3-ethoxypropionate	Sewage treatment plant	50 mg/l
	Fresh water	0.061 mg/l
	Sea water	0.006 mg/l
	Fresh water sediment	0.419 mg/kg
	Sea sediment	0.042 mg/kg
	Soil	0.048 mg/kg

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation.

#### Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.  
Safety glasses with side-shields conforming to EN166

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm  
Further information on penetration time is available from the manufacturer of the glove.  
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Request information on glove permeation properties from the glove supplier.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
Preventive skin protection  
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)  
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695	Date of first issue: 05.09.2024
		96	

- of permeation time according to EN ISO 374-1):  
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
- Skin and body protection : Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres. chemical-resistant disposable coveralls
- Respiratory protection : Suitable respiratory equipment:  
full face mask with AB2P3 class combination filter  
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Protective measures : Do not breathe vapour/spray.  
Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good industrial hygiene and safety practice.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid  
Color : colorless  
Odor : ester-like  
pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : not determined
- Boiling point/boiling range : 150.00 °C  
Flash point : 64 °C  
Method: ISO 3679
- Upper explosion limit / Upper flammability limit : not determined
- Lower explosion limit / Lower flammability limit : > 35.0 g/m3

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695 96	Date of first issue: 05.09.2024

---

Vapor pressure	:	6.0 hPa (20 °C) not determined (50 °C)
Density	:	1.110 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, kinematic	:	not determined (40 °C) 80.3 mm <sup>2</sup> /s (23 °C)
Flow time	:	> 60 s at 23 °C Cross section: 4 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Flammability (liquids)	:	Combustible liquid.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695 96	Date of first issue: 05.09.2024

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.  
Heat, flames and sparks.  
Avoid direct contact with water.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Harmful if inhaled.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 13.27 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

### Components:

#### **2-heptanone:**

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

#### **2-butoxyethyl acetate:**

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause respiratory irritation.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration toxicity**

Based on available data, the classification criteria are not met.

### Product:

No aspiration toxicity classification

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

### SECTION 12: Ecological information

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

##### Components:

##### **Hexamethylen-1,6-diisocyanat Homopolymer:**

Partition coefficient: n-octanol/water : log Pow: 9.81 (25 °C)

##### **Solvent naphtha (petroleum), light arom. (CAS EU: 128601-23-0):**

Partition coefficient: n-octanol/water : log Pow: 3.17  
GLP: no

##### **2-heptanone:**

Partition coefficient: n-octanol/water : log Pow: 2.26 (30 °C)  
pH: 7  
Method: Regulation (EC) No. 440/2008, Annex, A.8  
GLP: yes

##### **3,5,5-trimethylhexanoic acid:**

Partition coefficient: n-octanol/water : Pow: 1,580 (25 °C)  
log Pow: 3.2 (25 °C)  
pH: 3  
Method: OECD Test Guideline 117  
GLP: yes

##### **2-butoxyethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.51 (25 °C)  
pH: 7  
Method: OECD Test Guideline 107  
GLP: no

#### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695	Date of first issue: 05.09.2024
		96	

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Residues in empty containers should be neutralised with decontaminant (see section 6). Packaging that is not properly emptied must be disposed of as the unused product.

## SECTION 14: Transport information

### 14.1 UN number

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

---

### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.4 Packing group

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695	Date of first issue: 05.09.2024
		96	

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:  
Number on list 3, 20

Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 34 2015 (COMAH) : Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Volatile organic compounds (VOC) content: 188 g/l

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 15.45 %

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695	Date of first issue: 05.09.2024
		96	

Details relating to the VOC Directive 2004/42/EC:  
Subcategory as indicated in Annex IIB: dropped  
Limit value for maximum VOC content as specified in Annex IIB: dropped

### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitization
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version 2.2      Revision Date: 17.12.2025      SDS Number: 0000000000506695      Date of last issue: 07.06.2025  
Date of first issue: 05.09.2024  
96

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

### Classification of the mixture:

Acute Tox. 4      H332  
Eye Irrit. 2      H319  
Skin Sens. 1      H317  
STOT SE 3      H335

### Classification procedure:

Calculation method  
Calculation method  
Calculation method  
Calculation method

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## 50-510 0,5L Ambient Clear Hardener 0,5L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 07.06.2025
2.2	17.12.2025	0000000000506695 96	Date of first issue: 05.09.2024

---

Aquatic Chronic 3

H412

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN