

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 000000000050738621      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : baslac Ready Mix L45 AW45-05 1L 1L Metal can  
Product code : 000000000050738621

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Spraying  
Coatings and related products

#### 1.3 Details of the supplier of the safety data sheet

**Company:**

BASF Coatings France SAS  
Z.I de Breuil-Le-Sec, Rue André Pommery  
60480 Breuil-Le-Sec  
France

**Contact address:**

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
United Kingdom

---

Telephone: +44 161 475 3000  
E-mail address: product-safety-coatings@basf.com

---

#### 1.4 Emergency telephone

International emergency number:  
Telephone: +49 180 2273-112

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 0000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

1,2-Benzisothiazol-3(2H)-on	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  specific concentra- tion limit Skin Sens. 1; H317 >= 0.036 %	>= 0.0025 - < 0.025
2-methyl-2H-isothiazol-3-one	2682-20-4 220-239-6 613-326-00-9	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1  specific concentra- tion limit Skin Sens. 1A; H317 >= 0.0015 %	>= 0.0002 - < 0.0015
Substances with a workplace exposure limit :			
talc	14807-96-6 238-877-9		>= 25 - < 50

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386 21	Date of first issue: 16.08.2024

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
Move out of dangerous area.  
In all cases of doubt, or when symptoms persist, seek medical attention.  
Immediately remove contaminated clothing.  
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).  
First aid personnel should pay attention to their own safety.
- If inhaled : If breathed in, move person into fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
If symptoms persist, call a physician.
- In case of skin contact : If symptoms persist, call a physician.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Do NOT use solvents or thinners.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.  
Call a physician immediately.  
If easy to do, remove contact lens, if worn.
- If swallowed : Rinse mouth.  
Do NOT induce vomiting.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.  
No known specific antidote.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386 21	Date of first issue: 16.08.2024

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Dry powder  
Carbon dioxide (CO<sub>2</sub>)  
Water spray  
Foam

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

#### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Cool containers/tanks with water spray.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.  
Avoid breathing vapours.  
For non-emergency personnel:

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	000000000507386	Date of first issue: 16.08.2024
		21	

Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.  
Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.  
Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.  
Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.  
Avoid breathing vapours.  
For non-emergency personnel:  
Use personal protective equipment.  
Ensure adequate ventilation, especially in confined areas.  
Keep away from sources of ignition.  
For emergency responders:  
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

### 6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.  
Avoid subsoil penetration.  
Do not allow uncontrolled discharge of product into the environment.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386	Date of first issue: 16.08.2024
		21	

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
Ensure adequate ventilation.

### 6.4 Reference to other sections

For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapors or spray mist.  
Handle in accordance with good industrial hygiene and safety practice.  
Avoid contact with the skin, eyes and clothing.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.  
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.  
Do not return residues to the storage containers.  
Provide good ventilation of working area (local exhaust ventilation if necessary).  
Do not breathe vapors or spray mist.  
Handle in accordance with good industrial hygiene and safety practice.  
Avoid contact with the skin, eyes and clothing.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particu-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386	Date of first issue: 16.08.2024
		21	

lates and solvent vapour concentration has fallen below the exposure limits.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

Do not return residues to the storage containers.

Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not breathe vapors or spray mist.

Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with the skin, eyes and clothing.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

Do not return residues to the storage containers.

Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not breathe vapors or spray mist.

Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with the skin, eyes and clothing.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

Do not return residues to the storage containers.

Provide good ventilation of working area (local exhaust ventilation if necessary).

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	000000000507386	Date of first issue: 16.08.2024
		21	

Do not breathe vapors or spray mist.  
Handle in accordance with good industrial hygiene and safety practice.  
Avoid contact with the skin, eyes and clothing.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.  
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.  
Do not return residues to the storage containers.  
Provide good ventilation of working area (local exhaust ventilation if necessary).  
Provide good ventilation of working area (local exhaust ventilation if necessary).  
Do not return residues to the storage containers.  
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.  
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.  
The workplace should be equipped with an emergency shower and eye-rinsing facility.  
Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good industrial hygiene and safety practice.

Advice on protection against fire and explosion :

Do not breathe vapors or spray mist.  
Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

The relevant fire protection measures should be noted. Use

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

explosion-proof equipment.

The relevant fire protection measures should be noted. Use explosion-proof equipment.

The relevant fire protection measures should be noted. Use explosion-proof equipment.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Packaging material : Suitable material: Stove-lacquer RDL 50, Stove-lacquer R 78433, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer EHD0022, Standard interior paint, Stove-lacquer C222A/C221A, High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephthalate (PET), Polypropylene

### 7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
talc	14807-96-6	TWA (Respirable dust)	1 mg/m <sup>3</sup>	GB EH40
2-butoxyethanol	111-76-2	TWA	25 ppm 123 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 0000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
	STEL      50 ppm 246 mg/m3      GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
	TWA      20 ppm 98 mg/m3      2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative
	STEL      50 ppm 246 mg/m3      2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

## 8.2 Exposure controls

### Engineering measures

Ensure adequate ventilation.

### Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.  
Safety glasses with side-shields conforming to EN166

Hand protection

Remarks : Processes should be designed in such a way, that only disposable gloves against splashes are required, e.g. nitrile or neoprene gloves.  
In case of regular or extensive contact, a protection glove certified according to EN ISO 374-1 and made of butyl rubber (material thickness 0.5 mm) or nitrile rubber (material thickness 0,35 mm) or fluorinated rubber (material thickness 0,5 mm) is recommended.  
Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386	Date of first issue: 16.08.2024
		21	

---

Skin and body protection	:	time according to EN ISO 374-1)
Respiratory protection	:	Anti-static protective clothing
	:	Suitable respiratory equipment: half-mask with A1P2 class combination filter
	:	In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
	:	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Protective measures	:	Do not breathe vapour/spray.
	:	Eye wash fountains and safety showers must be easily accessible.
	:	If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.
	:	Avoid contact with the skin, eyes and clothing.
	:	Handle in accordance with good industrial hygiene and safety practice.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Appearance	:	liquid
Color	:	various
Odor	:	of glycol
pH	:	7.5 - 8.5
	:	substance/mixture is non-polar/aprotic
	:	substance/mixture is non-polar/aprotic
	:	substance/mixture is non-polar/aprotic
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	62 °C

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

---

Method: ISO 3679

Flammability : Combustible liquid.

Sustained combustibility : Sustains combustibility: yes

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : > 35 g/m<sup>3</sup>

Vapor pressure : not determined (20 °C)  
not determined (50 °C)

Relative vapor density : Lighter than air.  
Lighter than air.  
Lighter than air.

Density : 1.000 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : not determined  
Partition coefficient: n-octanol/water : not applicable for mixtures  
Autoignition temperature : > 200 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, kinematic : 97.3 mm<sup>2</sup>/s (23 °C)  
not determined (40 °C)

Flow time : > 72 s at 23 °C  
Cross section: 4 mm  
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386 21	Date of first issue: 16.08.2024

---

### 9.2 Other information

- Self-heating substances : The substance or mixture is not classified as self heating.
  - Metal corrosion rate : Not corrosive to metals.
  - Particle size : The substance / product is marketed or used in a non solid or granular form.
- 

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Avoid direct sunlight.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 0000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

### Components:

#### **2-butoxyethanol:**

Acute oral toxicity : LD50 (guinea pig): 1,200 mg/kg

#### **2-methyl-2H-isothiazol-3-one:**

Acute inhalation toxicity : LC50 (Rat, male and female): 0.11 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes

Assessment: Corrosive to the respiratory tract.

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

### **Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Based on available data, the classification criteria are not met.

#### **Respiratory sensitization**

Based on available data, the classification criteria are not met.

#### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 0000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration toxicity

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **2-methyl-2H-isothiazol-3-one:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **2-butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.81 (25 °C)  
GLP: no

##### **1,2-Benzisothiazol-3(2H)-on:**

Partition coefficient: n-octanol/water : log Pow: 0.7 (20 °C)  
GLP: yes

##### **2-methyl-2H-isothiazol-3-one:**

Partition coefficient: n-octanol/water : log Pow: -0.486 (25 °C)  
pH: 7  
Method: OECD Test Guideline 107  
GLP: yes

##### **talca:**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 0000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

Partition coefficient: n-octanol/water : log Pow: -9.4 (25 °C)  
pH: 7  
GLP: no

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

Additional ecological information : Avoid release to the environment.

Avoid release to the environment.

Avoid release to the environment.

Avoid release to the environment.

Avoid release to the environment.

Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 0000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

### SECTION 14: Transport information

#### 14.1 UN number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386 21	Date of first issue: 16.08.2024

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	:	Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 5 %

Volatile organic compounds (VOC) content: 420 g/l  
VOC content excluding water

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### 15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version 2.0      Revision Date: 06.03.2026      SDS Number: 0000000000507386      Date of last issue: 16.08.2024  
Date of first issue: 16.08.2024  
21

### SECTION 16: Other information

#### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H332 : Harmful if inhaled.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 BAT : UK. Biological monitoring guidance values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

## baslac Ready Mix L45 AW45-05 1L 1L Metal can

Version	Revision Date:	SDS Number:	Date of last issue: 16.08.2024
2.0	06.03.2026	0000000000507386	Date of first issue: 16.08.2024
		21	

Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : For multi-pack systems observe material safety data sheets of all components.  
Restricted to professional users.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN